

KASTEL MIDI



Ceiling or wall mounted, IP65 luminaire. Top quality SMD LED module with colour consistency MacAdams 3, extensive portfolio of lumen ranges, CCTs and spectra. Standard EVG integrated on/off driver. Mounting on any type of wall/ceiling. Body is made of aluminium. Standard colour RAL 7016 any other colour on request. Selection of lumen outputs allows to use this luminaire in different types of lighting projects. Standard luminaire is not intended for use in increased corrosivity category environment, e.g. with increased salt concentration. Extra corrosion protection is available on request.

Luminous flux & Luminaire Power tolerance up to 10%. System power consumption depends on components used. Luminous efficacy depends on type of LED's, electronics, optics and diffuser. The most up to date technical parameters can be found on our website and in database of LDT files.

Lighting direction



PDF datasheet:




KASTEL MIDI

Mounting:	Ceiling or Wall mounting (WL type)
Body material:	Aluminium
Colour:	Standard anthracite grey RAL 7016, other RAL colours on request
Lumen output:	Standard up to 1200 lm, any other on request
LED module:	Signify (Philips) SMD LED module, other on request
Colour temperature:	3000/4000K, other on request
Colour Rendering:	CRI>80 in standard, other on request
Driver:	EVG on-off integrated, other on request
Wireless controll:	N/A
Daylight/Occupancy sensor:	N/A
Emergency unit:	N/A
Operating temperature range:	-20°C ... +40°C
IP Class:	IP65 in standard
Power:	220-240V 50/60Hz
Lighting direction:	Direct lighting
Light distribution:	Symmetric
Optics:	N/A
Beam angle:	All types available in our LDT file database
Diffuser:	OP opal diffuser
Warranty:	5 Years standard warranty

KASTEL MIDI ceiling mounted luminaire

KASTEL MIDI WL wall mounted luminaire

All current index numbers, lumen outputs, power consumption and many other technical information are available in our 2024 pricelist.



Basic dimensions



KASTEL MIDI

Product code	Product name	Gross Lumen [lm]	Nett Lumen [lm]	Power [W]	Efficacy [lm/W]	Colour temperature [K]	Optics	Length [mm]	Width [mm]	Height [mm]	Nett Weight [kg]
70.00360.83.E.OP	KASTEL MIDI / 2000lm / 830 / E / OP	2000	1700	15	113	3000	Symmetrical	150	150	150	1,5
70.00360.84.E.OP	KASTEL MIDI / 2000lm / 840 / E / OP	2000	1700	15	113	4000	Symmetrical	150	150	150	1,5