

KASTEL MINI











Ceiling or wall mounted, IP65 luminaire. Top quality SMD LED module with colour consistency MacAdams 3, extensive portfolio of lumen ranges, CCTs and spectra. Standard EVG integrated on/off driver. Mounting on any type of wall/ceiling. Body is made of aluminium. Standard colour RAL 7016 any other colour on request. Selection of lumen outputs allows to use this luminaire in different types of lighting projects. Standard luminaire is not intended for use in increased corrosivity category environment, e.g. with increased salt concentration. Extra corrosion protection is available on request.

Luminous flux & Luminaire Power tolerance up to 10%. System power consumption depends on components used. Luminous efficacy depends on type of LED's, electronics, optics and diffusor. The most up to date technical parameters can be found on our website and in database of LDT files.

Lighting direction





PDF datasheet:





KASTEL MINI

Mounting: Ceiling or Wall mounting (WL type)

Body material: Aluminium

Colour: Standard anthracite grey RAL 7016, other RAL colours on request

 Lumen output:
 Standard up to 1200 lm, any other on request

 LED module:
 Signify (Philips) SMD LED module, other on request

Colour temperature: 3000/4000K, other on request

 Colour Rendering:
 CRI>80 in standard, other on request

 Driver:
 EVG on-off integrated, other on request

Wireless controll: N/A
Daylight/Occupancy sensor: N/A
Emergency unit: N/A

Operating temperature range: -20°C ... +40°C
IP Class: IP65 in standard
Power: 220-240V 50/60Hz
Lighting direction: Direct lighting
Light distribution: Symmetric
Optics: N/A


Beam angle: All types available in our LDT file database

Diffuser: OP opal diffuser

Warranty: 5 Years standard warranty

KASTEL MINI ceiling mounted luminaire
KASTEL MINI WL wall mounted luminaire

All current index numbers, lumen outputs, power consumption and many other technical information are available in our 2024 pricelist.



Basic dimensions