

# LUCERNA SLM




Recessed LED luminaire. Body is made of steel and aluminium and it is available in all RAL colours. Light source - Philips, Osram or Tridonic LED module. Standard EVG ballast, DALI or Touch Dali version on request. Passive cooling, optional IP44 diffuser and 3 hour emergency unit. Product is also available with special application LED modules: CrispWhite, Food WarmWhite, Food PremiumRed and many others - details on request.

High quality, energy efficient white LED light with CRI up to 97 Ra.

**Applications:**

- Retail: shop windows, wall - washing, accent and display lighting
- Hospitality: lobbies, reception areas, restaurants, bars, elevators
- Recreation: museums, galleries, theatres and other public places

Index no.	Lumen output	Wattage	Colour temp.	Colour rendering index	Lifetime	Weight
004805.1100/827	1100 lm	9 W	2700 K	Ra > 80	50.000 h	3,00 kg
004805.1100/830	1100 lm	9 W	3000 K	Ra > 80	50.000 h	3,00 kg
004805.1100/840	1100 lm	8 W	4000 K	Ra > 80	50.000 h	3,00 kg
004805.2000/827	2000 lm	16 W	2700 K	Ra > 80	50.000 h	3,00 kg
004805.2000/830	2000 lm	15 W	3000 K	Ra > 80	50.000 h	3,00 kg
004805.2000/840	2000 lm	14 W	4000 K	Ra > 80	50.000 h	3,00 kg
004805.3000/827	3000 lm	24 W	2700 K	Ra > 80	50.000 h	3,00 kg
004805.3000/830	3000 lm	23 W	3000 K	Ra > 80	50.000 h	3,00 kg
004805.3000/840	3000 lm	21 W	4000 K	Ra > 80	50.000 h	3,00 kg
004805.4500/830	4500 lm	36 W	3000 K	Ra > 80	50.000 h	3,00 kg
004805.4500/840	4500 lm	33 W	4000 K	Ra > 80	50.000 h	3,00 kg
004805.1100/927	1100 lm	11 W	2700 K	Ra > 90	50.000 h	3,00 kg
004805.1100/930	1100 lm	11 W	3000 K	Ra > 90	50.000 h	3,00 kg
004805.1100/940	1100 lm	10 W	4000 K	Ra > 90	50.000 h	3,00 kg
004805.2000/927	2000 lm	19 W	2700 K	Ra > 90	50.000 h	3,00 kg
004805.2000/930	2000 lm	19 W	3000 K	Ra > 90	50.000 h	3,00 kg
004805.2000/940	2000 lm	17 W	4000 K	Ra > 90	50.000 h	3,00 kg
004805.3000/927	3000 lm	28 W	2700 K	Ra > 90	50.000 h	3,00 kg
004805.3000/930	3000 lm	28 W	3000 K	Ra > 90	50.000 h	3,00 kg
004805.3000/940	3000 lm	25 W	4000 K	Ra > 90	50.000 h	3,00 kg
004805.4500/927	4500 lm	46 W	2700 K	Ra > 90	50.000 h	3,00 kg
004805.4500/930	4500 lm	44 W	3000 K	Ra > 90	50.000 h	3,00 kg
004805.4500/940	4500 lm	40 W	4000 K	Ra > 90	50.000 h	3,00 kg
004805.3000/930CW	3000 lm	34 W	3000 K	Ra > 90	50.000 h	3,00 kg
004805.3800/930CW	3800 lm	42 W	3000 K	Ra > 90	50.000 h	3,00 kg
004805.2800/925FW	3000 lm	42 W	2900K	Ra > 90	50.000 h	3,00 kg
004805.3000/930FR	3000 lm	42 W	3150K	Ra > 80	50.000 h	3,00 kg



\* Different lumen output or wattage available on request.  
 \* System power consumption (LED module & driver) depends on components used. Contact us for detailed information.  
 \* Available with spot, medium or flood reflector.

