

UNO FORTIMO



Recessed adjustable LED luminaire.



Body is made of steel and aluminium and it is available in all RAL colours.

Light source - Philips, Osram or Tridonic LED module. Standard EVG ballast, DALI or Touch Dali version on request. Passive cooling.

High quality, energy efficient white LED light with CRI 80 and more.

Applications:

- Retail: shop windows, wall - washing, accent and display lighting
- Hospitality: lobbies, reception areas, restaurants, bars, elevators
- Recreation: museums, galleries, theatres and other public places



Index no.	Lumen output	Wattage	Colour temp.	Colour rendering index	Lifetime	Weight
With integrated AC driver						
005267.1100/830	1100 lm	12 W	3000 K	Ra > 80	50.000 h	3,10 kg
005267.1100/840	1100 lm	12 W	4000 K	Ra > 80	50.000 h	3,10 kg
005267.2000/830	2000 lm	28 W	3000 K	Ra > 80	50.000 h	3,10 kg
005267.2000/840	2000 lm	26 W	4000 K	Ra > 80	50.000 h	3,10 kg
005267.3000/830	3000 lm	43 W	3000 K	Ra > 80	50.000 h	3,10 kg
005267.3000/840	3000 lm	39 W	4000 K	Ra > 80	50.000 h	3,10 kg
With AC/DC driver						
003058.1100/830	1100 lm	12 W	3000 K	Ra > 80	50.000 h	3,30 kg
003058.1100/840	1100 lm	12 W	4000 K	Ra > 80	50.000 h	3,30 kg
003058.2000/830	2000 lm	20 W	3000 K	Ra > 80	50.000 h	3,30 kg
003058.2000/840	2000 lm	20 W	4000 K	Ra > 80	50.000 h	3,30 kg
003058.3000/830	3000 lm	30 W	3000 K	Ra > 80	50.000 h	3,30 kg
003058.3000/840	3000 lm	30 W	4000 K	Ra > 80	50.000 h	3,30 kg

* Different lumen output or wattage available on request.

* System power consumption (LED module & driver) depends on components used. Contact us for detailed information.

