

## **BED FLEX**





Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6514.300/830	210	3	3000	Ra > 80	30.000	3	3	0,40
6514.300/840	210	3	4000	Ra > 80	30.000	3	3	0,40

## Wall mounted, adjustable LED luminaire

Wall mounted Mounting: Body material: Steel and aluminium

Standard White 9010, other

RAL colours on request ( please add RAL code after index Colour:

number)

Philips / Osram or Tridonic LED module included LED module:

2700K , 3000K or 4000K available Colour temperature:

Colour Rendering Index (CRI): >80 in standard, other on

request

Driver: Electronic driver

N/A Emergency unit: Movement sensor: N/A Daylight control sensor: N/A

Operating temperature range:

0°C ... +40°C

IP Class: IP20 in standard Power: 220-240V 50/60Hz

Direct lighting with possibility of light direction adjustment Lighting direction:

Reflector type: Integrated lens Light distribution: Symmetric

General data: 5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

