

## BS LED HH



Wall mounted, adjustable LED luminaire

<b>Mounting:</b>	Wall mounted
<b>Body material:</b>	Steel and aluminium
<b>Colour:</b>	Standard White 9010, other RAL colours on request ( please add RAL code after index number )
<b>LED module:</b>	Philips / Osram or Tridonic LED module included
<b>Colour temperature:</b>	2700K , 3000K or 4000K available
<b>Colour Rendering Index (CRI):</b>	>80 in standard, other on request
<b>Driver:</b>	Electronic driver
<b>Emergency unit:</b>	N/A
<b>Movement sensor:</b>	N/A
<b>Daylight control sensor:</b>	N/A
<b>Operating temperature range:</b>	0°C ... +40°C
<b>IP Class:</b>	IP20 in standard
<b>Power:</b>	220-240V 50/60Hz
<b>Lighting direction:</b>	Direct lighting with possibility of light direction adjustment
<b>Reflector type:</b>	Integrated lens
<b>Light distribution:</b>	Symmetric
<b>General data:</b>	5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5836.100/830	100	3	3000	Ra > 80	30.000	3	3	0,40
5836.100/840	100	3	4000	Ra > 80	30.000	3	3	0,40

