

CALISIA 1200



|--|--|

Index no.	Lumen output [Im]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5770.7200/827	7200	81	2700	Ra > 80	50.000	5	4	12,00

Pendant LED luminaire.

Mounting:

Body material:

Colour:

LED module:

Colour temperature: Colour Rendering Index (CRI)

Driver: Emergency unit:

Movement sensor:

Daylight control sensor:

Operating temperature range:

IP Class:

Power:

Lighting direction:

Reflector type: Light distribution:

General data:

3 Years standard warranty Different lumen output or wattage available on request

Suspended on 1,5m long steel wire suspension (with wire length control)

Philips retrofit E27 LED bulb

Steel and aluminium Standard Black 9005, other RAL colours on request (please add RAL code after index

number)

2700K

N/A

N/A

N/A

N/A

IP20

N/A

0°C...+40°C

220-240V 50/60Hz

Direct lighting


Symmetric

>80 in standard

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



IMPERIAL reserves rights to introduce any construction or technical changes in the products. Wattage of products may vary due to constant LED efficacy improvements.