

## CALISIA 900



Pendant LED luminaire.

<b>Mounting:</b>	Suspended on 1,5m long steel wire suspension ( with wire length control )
<b>Body material:</b>	Steel and aluminium
<b>Colour:</b>	Standard Black 9005, other RAL colours on request ( please add RAL code after index number )
<b>LED module:</b>	Philips retrofit E27 LED bulb
<b>Colour temperature:</b>	2700K
<b>Colour Rendering Index (CRI)</b>	>80 in standard
<b>Driver:</b>	N/A
<b>Emergency unit:</b>	N/A
<b>Movement sensor:</b>	N/A
<b>Daylight control sensor:</b>	N/A
<b>Operating temperature range:</b>	0°C ... +40°C
<b>IP Class:</b>	IP20
<b>Power:</b>	220-240V 50/60Hz
<b>Lighting direction:</b>	Direct lighting
<b>Reflector type:</b>	N/A
<b>Light distribution:</b>	Symmetric
<b>General data:</b>	3 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6519.4800/827	4800	54	2700	Ra > 80	50.000	5	4	8,90

