






Drawing





Energy saving MasterConnect wireless lighting control system with daylight and movement detection technology on request.





CLEANEO 600 SURF 4PL

Surface mounted IP65 LED luminaire.

Directly on the ceiling Mountina: Body material: Steel and aluminium

Colour: Standard White RAL 9016, other RAL colours on request Signify (Philips) or equivalent LED module included LED module:

3000K/4000K/Tunable White Colour temperature:

Colour Rendering Index

(CRI):

>80 in standard, >90 on request

Driver: EVG/DALI/MasterConnect on request

Emergency unit: on request Movement sensor: on request Daylight control sensor: on request Operating temperature

range:

0°C ... +40°C

IP Class: IP65

220-240V 50/60Hz Power: Lighting direction: Direct lighting Parabolic louver Reflector type: Light distribution: Symmetric Diffuser: Clear glass

General data: 5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our

pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power

tolerance +/- 10%.

System power consumption (LED module & driver)

depends on components used

Efficacy depends on type of LED's, electronics, optics and diffusor and may differ from shown in our data pages. Most up to date information can be found in our lighting

data file database.



Available versions



CLEANEO 600 SURF 4PL

Product code	Product name	Gross Lumen [lm]	Nett Lumen [lm]	Power [W]	Efficacy [lm/W]	Colour temperature [K]	Length [mm]	Width [mm]	Height [mm]	Nett Weight [kg]
Surface mounted luminaire with 4 rows of parabolic louvers and clear glass diffuser										
12.00190.83.E.ML.CG	CLEANEO 600 SURF 4PL/8800 lm/830/E/ML/CG	8800	7450	60	124	3000	600	600	50	7,00
12.00190.84.E.ML.CG	CLEANEO 600 SURF 4PL/8800 lm/840/E/ML/CG	8800	7450	60	124	4000	600	600	50	7,00
12.00190.83.DA.ML.CG	CLEANEO 600 SURF 4PL/8800 lm/830/DA/ML/CG	8800	7450	60	124	3000	600	600	50	7,00
12.00190.83.DA.ML.CG	CLEANEO 600 SURF 4PL/8800 lm/840/DA/ML/CG	8800	7450	60	124	4000	600	600	50	7,00