



CLIN 1200 OP


Recessed IP65 LED luminaire for mounting in modular ceiling, version for gypsum ceiling on request.

Mounting:	Modular ceiling lay in type in standard, option for gypsum ceiling on request.
Body material:	Steel and aluminium
Colour:	Standard White RAL 9016, other RAL colours on request
LED module:	Signify (Philips) or equivalent LED module included
Colour temperature:	3000K/4000K/Tunable White
Colour Rendering Index (CRI):	>80 in standard, >90 on request
Driver:	EVG/DALI/MasterConnect on request
Emergency unit:	on request
Movement sensor:	on request
Daylight control sensor:	on request
Operating temperature range:	0°C ... +40°C
IP Class:	IP65
Power:	220-240V 50/60Hz
Lighting direction:	Direct lighting
Reflector type:	Parabolic louver
Light distribution:	Symmetric
Diffuser:	Clear glass with opalic film
General data:	5 Years standard warranty

IP65 220-240 V 50-60 Hz



Drawing



Energy saving MasterConnect wireless lighting control system with daylight and movement detection technology on request.



Zigbee



Bluetooth

Different lumen output or wattage available on request


All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

Efficacy depends on type of LED's, electronics, optics and diffusor and may differ from shown in our data pages. Most up to date information can be found in our lighting data file database.

Available versions



CLIN 1200 OP

Product code	Product name	Gross Lumen [lm]	Nett Lumen [lm]	Power [W]	Efficacy [lm/W]	Colour temperature [K]	Length [mm]	Width [mm]	Height [mm]	Nett Weight [kg]
Recessed luminaire lay-in type for modular ceiling with opalic glass diffuser										
12.00150.83.E.OP.CG	CLIN 1200 OP/10000lm/830/E/OP/CG	10000	8500	60	142	3000	1195	595	75	16,00
12.00150.84.E.OP.CG	CLIN 1200 OP/10000lm/840/E/OP/CG	10000	8500	60	142	4000	1195	595	75	16,00
12.00150.83.DA.OP.CG	CLIN 1200 OP/10000lm/830/DA/OP/CG	10000	8500	60	142	3000	1195	595	75	16,00
12.00150.83.DA.OP.CG	CLIN 1200 OP/10000lm/840/DA/OP/CG	10000	8500	60	142	4000	1195	595	75	16,00