

CONO 3 IP54



Suspended IP54 LED luminaire.

| | |
|-------------------------------------|--|
| Mounting: | Suspended from the ceiling |
| Body material: | Aluminium, steel, stainless steel |
| Colour: | Standard Black RAL 9005, other RAL colours on request (please add RAL code after index number) |
| LED module: | Osram LED module included |
| Colour temperature: | 3000K or 4000K |
| Colour Rendering Index (CRI) | >80 in standard |
| Driver: | Electronic integrated driver in standard |
| Emergency unit: | N/A |
| Movement sensor: | N/A |
| Daylight control sensor: | N/A |
| Operating temperature range: | minus 20°C ... +40°C |
| IP Class: | IP54 |
| Power: | 220-240V 50/60Hz |
| Lighting direction: | Direct |
| Reflector type: | Aluminium white |
| Light distribution: | Symmetric |
| General data: | 5 Years standard warranty |
| | Different lumen output or wattage available on request |
| | All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist |
| | Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%. |
| | System power consumption (LED module & driver) depends on components used |



| Index no. | Lumen output [lm] | Power [W] | Colour temp. [K] | CRI | Lifetime [H] | Warranty [Years] | MacAdam [SDCM] | Weight [kg] |
|---------------|-------------------|-----------|------------------|---------|--------------|------------------|----------------|-------------|
| 5842.2500/830 | 2500 | 21 | 3000 | Ra > 80 | 50.000 | 5 | 3 | 2,00 |
| 5842.2500/840 | 2500 | 21 | 4000 | Ra > 80 | 50.000 | 5 | 3 | 2,00 |

