

## DLK 200



Recessed LED downlight for installation in suspended ceilings.

<b>Mounting:</b>	Ceiling recessed, mounting brackets included
<b>Body material:</b>	Steel and aluminium
<b>Colour:</b>	Standard White RAL 9016, other RAL colours on request (please add RAL colour after index number)
<b>LED module:</b>	Signify (Philips), Osram, Tridonic or equivalent LED module included
<b>Colour temperature:</b>	3000 / 4000K, other on request
<b>Colour Rendering Index (CRI)</b>	>80 in standard, other on request
<b>Driver:</b>	Electronic driver in standard, DALI on request
<b>Emergency unit:</b>	N/A
<b>Movement sensor:</b>	N/A
<b>Daylight control sensor:</b>	N/A
<b>Operating temperature range:</b>	0°C ... +40°C
<b>IP Class:</b>	IP44
<b>Power:</b>	220-240V 50/60Hz
<b>Lighting direction:</b>	Direct lighting
<b>Reflector type:</b>	Aluminium glossy
<b>Light distribution:</b>	Symmetric
<b>Diffuser:</b>	Altuglas [ ALT ] opalic diffuser in standard
<b>General data:</b>	5 Years standard warranty, possible extension with project registration

Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

Efficacy depends on type of LED's, electronics, optics and diffuser and may differ from shown in our data pages. Most up to date information can be found in our lighting data file database.



Index no.	Net lumen output [lm]	Gross lumen output [lm]	Efficacy [lm/W]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	MacAdam [SDCM]	Weight [kg]
With integrated AC driver									
6500.1100/830	970	1100	97	10	3000	Ra > 80	50.000	3	2,10
6500.1100/840	970	1100	97	10	4000	Ra > 80	50.000	3	2,10
6500.2000/830	1600	2000	89	18	3000	Ra > 80	50.000	3	2,10
6500.2000/840	1600	2000	89	18	4000	Ra > 80	50.000	3	2,10
6500.3000/830	2400	3000	89	27	3000	Ra > 80	50.000	3	2,10
6500.3000/840	2400	3000	89	27	4000	Ra > 80	50.000	3	2,10
With AC/DC driver									
6563.1300/830	970	1300	81	12	3000	Ra > 80	50.000	3	2,30
6563.1300/840	970	1300	81	12	4000	Ra > 80	50.000	3	2,30
6563.2100/830	1600	2100	84	19	3000	Ra > 80	50.000	3	2,30
6563.2100/840	1650	2100	87	19	4000	Ra > 80	50.000	3	2,30
6563.3200/830	2500	3200	86	29	3000	Ra > 80	50.000	3	2,30
6563.3200/840	2500	3200	86	29	4000	Ra > 80	50.000	3	2,30

