

## DLN 120 X EMPIRE



Pendant LED luminaire

<b>Mounting:</b>	Suspended on 1,5m long steel wire suspension ( with wire length control )
<b>Body material:</b>	Steel and aluminium
<b>Colour:</b>	Standard Gray 9006, other RAL colours on request ( please add RAL code after index number )
<b>LED module:</b>	Philips / Osram or Tridonic LED module
<b>Colour temperature:</b>	2700K, 3000K or 4000K
<b>Colour Rendering Index (CRI):</b>	>80 in standard, other on request
<b>Driver:</b>	Electronic driver in standard, DALI on request
<b>Emergency unit:</b>	N/A
<b>Movement sensor:</b>	N/A
<b>Daylight control sensor:</b>	N/A
<b>Operating temperature range:</b>	0°C... +40°C
<b>IP Class:</b>	IP20
<b>Power:</b>	220-240V 50/60Hz
<b>Lighting direction:</b>	Direct lighting
<b>Reflector type:</b>	Aluminium glossy
<b>Light distribution:</b>	Symmetric
<b>General data:</b>	5 Years standard warranty

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
4771.1100/827	1100	9	2700	Ra > 80	50.000	5	3	10,00
4771.1100/830	1100	9	3000	Ra > 80	50.000	5	3	10,00
4771.1100/840	1100	9	4000	Ra > 80	50.000	5	3	10,00
4771.2400/827	2400	20	2700	Ra > 80	50.000	5	3	10,00
4771.2400/830	2400	20	3000	Ra > 80	50.000	5	3	10,00
4771.2400/840	2400	20	4000	Ra > 80	50.000	5	3	10,00
4771.3200/827	3200	28	2700	Ra > 80	50.000	5	3	10,00
4771.3200/830	3200	28	3000	Ra > 80	50.000	5	3	10,00
4771.3200/840	3200	28	4000	Ra > 80	50.000	5	3	10,00

