

DLN V 140 IP54



Surface mounted IP54 LED luminaire.

Mounting:	Directly on the ceiling
Body material:	Aluminium and steel
Colour:	Standard Gray RAL 9006, other RAL colours on request (please add RAL code after index number)
LED module:	LED GU10 retrofit lamp included
Colour temperature:	2700K, 3000K or 4000K available
Colour Rendering Index (CRI):	>80 in standard
Driver:	N/A
Emergency unit:	N/A
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	- 20°C ... +40°C
IP Class:	IP54
Power:	220-240V 50/60Hz
Lighting direction:	Direct
Reflector type:	Aluminium glossy
Light distribution:	Symmetric
Diffuser:	Clear glass, any other on request
General data:	3 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3326.355/827/36D	355	4,6	2700	Ra > 80	15.000	3	4	1,20
3326.370/830/36D	370	4,6	3000	Ra > 80	15.000	3	4	1,20
3326.390/840/36D	390	4,6	4000	Ra > 80	15.000	3	4	1,20

