

FLAT 600 LED PND

Pendant flat panel LED luminaire.

Mounting:	Suspended on 1,5m long steel wire suspension (with wire length control)
Body material:	Steel and aluminium
Colour:	Standard White, other RAL colours on request (please add RAL code after index number)
LED module:	Signify (Philips) or equivalent
Colour temperature:	3000 / 4000K, other on request
Colour Rendering Index (CRI):	>80 in standard
Driver:	Electronic driver in standard, other on request
Emergency unit:	N/A
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	0°C ... +40°C
IP Class:	IP20 in standard, IP44 on request
Power:	220-240V 50/60Hz
Lighting direction:	Direct lighting
Reflector type:	N/A
Light distribution:	Symmetric
Diffuser:	[WD] white opalic in standard, Microprismatic [MPR] on request
General data:	5 Years standard warranty Different lumen output or wattage available on request



Index no.	Net lumen output [lm]	Gross lumen output [lm]	Efficacy [lm/W]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	MacAdam [SDCM]	Weight [kg]
7591.3000/830	2900	3000	97	30	3000	Ra > 80	50.000	4	2,70
7591.3000/840	2900	3000	97	30	4000	Ra > 80	50.000	4	2,70
UGR < 19									
7613.3300/830	3200	3300	97	33	3000	Ra > 80	50.000	4	2,70
7613.3300/840	3200	3300	97	33	4000	Ra > 80	50.000	4	2,70

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

Efficacy depends on type of LED's, electronics, optics and diffuser and may differ from shown in our data pages. Most up to date information can be found in our lighting data file database.

