

GLOBO 500 XC

Pendant LED luminaire with EasyAir daylight&presence lighting control system.

Mounting:	Suspended on 1,5m long suspension
Body material:	Steel and aluminium
Colour:	Standard White RAL 9016, other RAL colours on request (please add RAL colour after index number)
LED module:	Signify (Philips), Osram, Tridonic or equivalent LED module included
Colour temperature:	3000K or 4000K, other on request
Colour Rendering Index (CRI):	>80 in standard, other on request
Driver:	Xitanium SR
Emergency unit:	On request
Movement sensor:	EasyAir sensor included
Daylight control sensor:	EasyAir sensor included
Operating temperature range:	0°C ... +40°C
IP Class:	IP20 in standard, IP44 on request
Power:	220-240V 50/60Hz
Lighting direction:	Direct
Light distribution:	Symmetric
Diffuser:	OP (Opal), MP (Microprismatic), MP19 (Microprismatic with UGR<19)
General data:	5 Years standard warranty

Different lumen output or wattage available on request


All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.


System power consumption (LED module & driver) depends on components used

Efficacy depends on type of LED's, electronics, optics and diffuser and may differ from shown in our data pages.

Most up to date information can be found in our lighting data file database.




Drawing



Energy saving EasyAir daylight and movement detection technology inside

Zigbee Bluetooth

Available versions



GLOBO 500 XC

Product code	Product name	Gross Lumen [lm]	Nett Lumen [lm]	Power [W]	Efficacy [lm/W]	Colour temperature [K]	Length [mm]	Height [mm]	Nett Weight [kg]
Suspended luminaire, light down									
50.01100.83.XC.OP	GLOBO 500 XC/5500lm/830/XC/OP	5500	4428	35	127	3000	Ø 500	280	4,9
50.01100.84.XC.OP	GLOBO 500 XC/5500lm/840/XC/OP	5500	4428	35	127	4000	Ø 500	280	4,9
50.01100.83.XC.MP	GLOBO 500 XC/5500lm/830/XC/MP	5500	4125	35	118	3000	Ø 500	280	4,9
50.01100.84.XC.MP	GLOBO 500 XC/5500lm/840/XC/MP	5500	4125	35	118	4000	Ø 500	280	4,9
50.01100.83.XC.MP19	GLOBO 500 XC/5500lm/830/XC/MP19	5500	4125	35	118	3000	Ø 500	280	4,9
50.01100.84.XC.MP19	GLOBO 500 XC/5500lm/840/XC/MP19	5500	4125	35	118	4000	Ø 500	280	4,9