

KING SIZE NEW PND



Pendant LED luminaire

Mounting:	Suspended on 1,5m long steel wire suspension (with wire length control)
Body material:	Steel, aluminium, acrylic tube
Colour:	Standard White RAL 9016, other RAL colours on request (please add RAL code after index number)
LED module:	Signify (Philips), Osram, Tridonic or equivalent LED module included
Colour temperature:	3000 / 4000K, other on request.
Colour Rendering Index (CRI):	>80 in standard other on request
Driver:	Electronic driver in standard, DALI on request
Emergency unit:	N/A
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	0°C ... +40°C
IP Class:	IP20
Power:	220-240V 50/60Hz
Lighting direction:	Direct lighting, direct / indirect on request
Reflector type:	N/A
Light distribution:	Symmetric
General data:	5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

Efficacy depends on type of LED's, electronics, optics and diffusor and may differ from shown in our data pages. Most up to date information can be found in our lighting data file database.



Index no.	Net lumen output [lm]	Gross lumen output [lm]	Efficacy [lm/W]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	MacAdam [SDCM]	Weight [kg]
6816.4400/830	3800	4400	136	28	3000	Ra > 80	50.000	3	1,60
6816.4400/840	3800	4400	136	28	4000	Ra > 80	50.000	3	1,60
6816.5500/830	4700	5500	138	34	3000	Ra > 80	50.000	3	1,60
6816.5500/840	4700	5500	138	34	4000	Ra > 80	50.000	3	1,60

