

# LENTE SQ R

Recessed LED luminaire with UGR<19 for mounting in suspended ceiling.

<b>Mounting:</b>	Recessed
<b>Body material:</b>	Steel and aluminium
<b>Colour:</b>	Standard White RAL 9016, other RAL colours on request (please add RAL colour after index number)
<b>LED module:</b>	Signify (Philips) or equivalent LED module included
<b>Colour temperature:</b>	3000K or 4000K
<b>Colour Rendering Index (CRI):</b>	>80 in standard, >90 on request
<b>Driver:</b>	EVG/DALI/DT8 on request
<b>Emergency unit:</b>	N/A
<b>Movement sensor:</b>	on request
<b>Daylight control sensor:</b>	on request
<b>Operating temperature range:</b>	0°C ... +40°C
<b>IP Class:</b>	IP20
<b>Power:</b>	220-240V 50/60Hz
<b>Lighting direction:</b>	Direct lighting
<b>Reflector type:</b>	Selection of lenses
<b>Light distribution:</b>	Symmetric/asymmetric
<b>General data:</b>	5 Years standard warranty, possible extension with project registration


Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist


Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

Efficacy depends on type of LED's, electronics, optics and diffusor and may differ from shown in our data pages. Most up to date information can be found in our lighting data file database.




## Drawing



Energy saving MasterConnect wireless lighting control system with daylight and movement detection technology on request.



## Available versions



### LENTE SQ R

Product code	Product name	Gross Lumen [lm]	Nett Lumen [lm]	Power [W]	Efficacy [lm/W]	Colour temperature [K]	Optics	Length [mm]	Width [mm]	Height [mm]	Nett Weight [kg]
<b>Surface mounted LED luminaire, LEDIL Daisy lens</b>											
40.01500.83.E.80.LNS	LENTE SQ R/1100 lm/830/E/LNS 80	1100	968	7	138	3000	80°	105	105	50	0,30
40.01500.83.E.50.LNS	LENTE SQ R/1100 lm/830/E/LNS 50	1100	968	7	138	3000	50°	105	105	50	0,30
40.01500.84.E.80.LNS	LENTE SQ R/1100 lm/840/E/LNS 80	1100	968	7	138	4000	80°	105	105	50	0,30
40.01500.84.E.50.LNS	LENTE SQ R/1100 lm/840/E/LNS 50	1100	968	7	138	4000	50°	105	105	50	0,30
40.01501.83.E.80.LNS	LENTE SQ R/2000 lm/830/E/LNS 80	2000	1760	14	126	3000	80°	105	105	50	0,30
40.01501.83.E.50.LNS	LENTE SQ R/2000 lm/830/E/LNS 50	2000	1760	14	126	3000	50°	105	105	50	0,30
40.01501.84.E.80.LNS	LENTE SQ R/2000 lm/840/E/LNS 80	2000	1760	14	126	4000	80°	105	105	50	0,30
40.01501.84.E.50.LNS	LENTE SQ R/2000 lm/840/E/LNS 50	2000	1760	14	126	4000	50°	105	105	50	0,30