

LINEA PL

Surface mounted or suspended LED luminaire with direct lighting.

Mounting:	Suspended on 1,5m long steel wire suspension (with wire length control)
Body material:	Steel and aluminium
Colour:	Standard White RAL 9016, other RAL colours on request (please add RAL colour after index number)
LED module:	Signify (Philips), Osram, Tridonic or equivalent LED module included
Colour temperature:	3000/4000K, other on request
Colour Rendering Index (CRI):	>80 in standard, other on request
Driver:	EVG/DALI on request
Emergency unit:	On request - Standard or DALI 3 hour emergency unit
Movement sensor:	on request
Daylight control sensor:	on request
Operating temperature range:	0°C ... +40°C
IP Class:	IP20 in standard
Power:	220-240V 50/60Hz
Lighting direction:	Direct lighting
Reflector type:	Aluminium glossy or mat on request
Light distribution:	Symmetric
Diffuser:	Parabolic louver
General data:	5 Years standard warranty


Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist


Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

Efficacy depends on type of LED's, electronics, optics and diffuser and may differ from shown in our data pages. Most up to date information can be found in our lighting data file database.





Drawing



Energy saving MasterConnect wireless lighting control system with daylight and movement detection technology on request.



Available versions



LINEA PL

Product code	Product name	Gross Lumen [lm]	Nett Lumen [lm]	Power [W]	Efficacy [lm/W]	Colour temperature [K]	Length [mm]	Width [mm]	Height [mm]	Nett Weight [kg]
Ceiling mounted luminaire, light down										
20.00250.83.E.ML	LINEA PL 4400lm/830/E/ML	4400	3300	26	127	3000	1220	175	60	5
20.00250.84.E.ML	LINEA PL 4400lm/840/E/ML	4400	3300	26	127	4000	1220	175	60	5
20.00251.83.E.ML	LINEA PL 5500lm/830/E/ML	5500	4125	33	125	3000	1500	175	60	6,5
20.00251.84.E.ML	LINEA PL 5500lm/840/E/ML	5500	4125	33	125	4000	1500	175	60	6,5
Suspended, light down (suspension set and power cable with ceiling cup included)										
20.00255.83.E.ML	LINEA PL PND 4400lm/830/E/ML	4400	3300	26	127	3000	1220	175	60	5
20.00255.84.E.ML	LINEA PL PND 4400lm/840/E/ML	4400	3300	26	127	4000	1220	175	60	5
20.00256.83.E.ML	LINEA PL PND 5500lm/830/E/ML	5500	4125	33	125	3000	1500	175	60	6,5
20.00256.84.E.ML	LINEA PL PND 5500lm/840/E/ML	5500	4125	33	125	4000	1500	175	60	6,5