# NANO PARK

Wall mounted LED luminaire

| | |
|---|---|
| **Mounting:** | Wall recessed |
| **Body material:** | Steel and aluminium |
| **Colour:** | Standard White RAL 9016, other RAL colours on request ( please add RAL code after index number ) |
| **LED module:** | LED module included |
| **Colour temperature:** | 2700K |
| **Colour Rendering Index (CRI):** | >80 |
| **Driver:** | Electronic driver included |
| **Emergency unit:** | N/A |
| **Movement sensor:** | N/A |
| **Daylight control sensor:** | N/A |
| **Operating temperature range:** | 0°C ... +40°C |
| **IP Class:** | IP20 |
| **Power:** | 220-240V 50/60Hz |
| **Lighting direction:** | Direct |
| **Reflector type:** | N/A |
| **Light distribution:** | Symmetric |
| **General data:** | 3 Years standard warranty |
| | Different lumen output or wattage available on request |
| | All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist |
| | Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%. |

IP20 220-240 V 50-60 Hz

| Index no. | Lumen output [lm] | Power [W] | Colour temp. [K] | CRI | Lifetime [H] | Warranty [Years] | MacAdam [SDCM] | Weight [kg] |
|---|---|---|---|---|---|---|---|---|
| 6516.140/830 | 140 | 3 | 3000 | Ra > 80 | 30.000 | 3 | 3 | 0,40 |
| 6516.140/840 | 140 | 3 | 4000 | Ra > 80 | 30.000 | 3 | 3 | 0,40 |




IMPERIAL reserves rights to introduce any construction or technical changes in the products.
Wattage of products may vary due to constant LED efficacy improvements.