OUTDOOR STRIPE

Recessed IP54 LED luminaire for installation in suspended ceilings.

Mounting:	Ceiling recessed, mounting brackets included
Body material:	Aluminium and steel
Colour:	Standard Gray 9006, other RAL colours on request (please add RAL code after index number)
LED module:	Philips / Osram or Tridonic LED module included
Colour temperature:	3000K or 4000K
Colour Rendering Index (CRI):	>80 in standard other on request
Driver:	On request
Emergency unit:	On request
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	- 20˚C ... +40˚C
IP Class:	IP54
Power:	220-240V 50/60Hz
Lighting direction:	Direct lighting
Reflector type:	Aluminium white
Light distribution:	Symmetric
Diffuser:	Mat glass in standard, other on request
General data:	5 Years standard warranty
	Different lumen output or wattage available on request
	All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist
	Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.
	System power consumption (LED module & driver) depends on components used

IP54 220-240 V 50-60 Hz

Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Length [mm]	Weight [kg]
2420.4400/830	4400	29	3000	Ra > 80	50.000	5	3	1170	5,00
2420.4400/840	4400	29	4000	Ra > 80	50.000	5	3	1170	5,00
2420.5500/830	5500	36	3000	Ra > 80	50.000	5	3	1450	6,50
2420.5500/840	5500	36	4000	Ra > 80	50.000	5	3	1450	6,50





IMPERIAL reserves rights to introduce any construction or technical changes in the products.
Wattage of products may vary due to constant LED efficacy improvements.