

POLE X 1400 LED



Outdoor IP65 LED luminaire.

Mounting:	On the ground, by direct mounting base or concrete mounting base - details below
Body material:	Aluminium and PMMA Acrylic tube
Colour:	Standard gray RAL 9006, other RAL colours on request (please add RAL code after index number)
LED module:	Osram LED module included
Colour temperature:	3000K or 4000K
Colour Rendering Index (CRI)	>80 in standard
Driver:	Electronic integrated driver
Emergency unit:	N/A
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	- 20°C ... +40°C
IP Class:	IP65
Power:	220-240V 50/60Hz
Lighting direction:	Direct lighting
Reflector type:	N/A
Light distribution:	Symmetric
Diffuser:	Mat acrylic diffuser
General data:	5 Years standard warranty

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

Efficacy depends on type of LED's, electronics, optics and diffuser and may differ from shown in our data pages. Most up to date information can be found in our lighting data file database.



Index no.	Net lumen output [lm]	Gross lumen output [lm]	Efficacy [lm/W]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	MacAdam [SDCM]	Weight [kg]
7292.1200/830/40D	600	1200	38	16	3000	Ra > 80	35.000	4	16,70
7292.1200/840/40D	600	1200	38	16	4000	Ra > 80	35.000	4	16,70
7292.1800/830/40D	900	1800	39	23	3000	Ra > 80	35.000	4	16,70
7292.1800/840/40D	900	1800	39	23	4000	Ra > 80	35.000	4	16,70

Mounting base

