

PROFI 48 POINT



Available versions




BESPOKE SIZE & PRODUCT FEATURES AVAILABLE

Index no.	Net lumen output [lm]	Gross lumen output [lm]	Efficacy [lm/W]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	MacAdam [SDCM]	Length [mm]	Weight [kg]
PROFI 48 POINT 4										
7397.550/830	300	550	43	7	3000	Ra > 80	50.000	3	1200	2,50
7397.550/840	300	550	43	7	4000	Ra > 80	50.000	3	1200	2,50

Additional adjustable spots on request



Number of lighting points with lenses can be customized



Surface mounted or suspended luminaire with linear and spot LEDs. Standard size shown in table below. Product can be made to measure and connected into lighting systems according to project requirements.

Mounting:	Directly on the wall
Body material:	Aluminium profile
Colour:	Standard Gray 9006, other RAL colours on request ( please add RAL code after index number )
LED module:	Signify (Philips), Osram, Tridonic or equivalent LED module included
Colour temperature:	3000K or 4000K, other on request
Colour Rendering Index (CRI)	>80 in standard, other on request
Driver:	Electronic driver in standard, DALI on request
Emergency unit:	on request - Standard or DALI 3 hour emergency unit
Movement sensor:	On request
Daylight control sensor:	On request
Operating temperature range:	0°C ... +40°C
IP Class:	IP20 in standard, IP44 on request
Power:	220-240V 50/60Hz
Lighting direction:	Direct
Reflector type:	Aluminium white / integrated lenses
Light distribution:	Symmetric
Diffuser:	[WD] white opalic in standard, Microprismatic [MPR] on request
General data:	5 Years standard warranty

Luminaires can be connected into long lighting lines

Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

Efficacy depends on type of LED's, electronics, optics and diffuser and may differ from shown in our data pages. Most up to date information can be found in our lighting data file database.