


PROFI R 60 LED SR




Luminaire is equipped with EasyAir Sensor:
 Communication between luminaires without wires
 Easy smartphone commissioning
 Enables gateway data readout
 Xitanium SR interface (based on DALI 2.0)

Available versions





- L - 655 x 64
- L - 940 x 64
- L - 1220 x 64
- L - 1500 x 64



Available diffusers:

[WD] diffuser

[MPR] diffuser



Recessed LED luminaire with Philips LED modules, Xitanium SR Dali 2.0 standard driver and EasyAir sensor. Can be made to measure or connected into lighting systems according to project requirements.

- Mounting:** Ceiling recessed, mounting brackets included
- Body material:** Aluminium profile
- Colour:** Standard Gray 9006, other RAL colours on request (please add RAL code after index number)
- LED module:** Signify (Philips) or equivalent LED module included
- Colour temperature:** 3000K or 4000K in standard, other on request
- Colour Rendering Index (CRI)** >80 in standard, other on request
- Driver:** Xitanium SR
- Emergency unit:** on request - Standard or DALI 3 hour emergency unit
- Movement sensor:** EasyAir sensor included
- Daylight control sensor:** EasyAir sensor included
- Operating temperature range:** 0°C... +40°C
- IP Class:** IP20
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct lighting
- Reflector type:** Aluminium white
- Light distribution:** Symmetric
- Diffuser:** [WD] white opalic in standard, Microprismatic [MPR] on request
- General data:** 5 Years standard warranty

UGR <19 diffuser on request

Luminaires can be connected into long lighting lines

Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

Efficacy depends on type of LED's, electronics, optics and diffuser and may differ from shown in our data pages. Most up to date information can be found in our lighting data file database.



Index no.	Net lumen output [lm]	Gross lumen output [lm]	Efficacy [lm/W]	LED Power [W]	Colour temp. [K]	Colour tolerance [MacAdam]	CRI	Lifetime [h]	Length / Size [mm]	Weight [kg]
6264.SR.2200/830/WD	1450	2200	104	14	3000	3	Ra > 80	50.000	670	1,50
6264.SR.2200/840/WD	1450	2200	104	14	4000	3	Ra > 80	50.000	670	1,50
6264.SR.3300/830/WD	2300	3300	105	22	3000	3	Ra > 80	50.000	951	2,00
6264.SR.3300/840/WD	2300	3300	105	22	4000	3	Ra > 80	50.000	951	2,00
6264.SR.4400/830/WD	3000	4400	107	28	3000	3	Ra > 80	50.000	1232	2,50
6264.SR.4400/840/WD	3000	4400	107	28	4000	3	Ra > 80	50.000	1232	2,50
6264.SR.5500/830/WD	3800	5500	112	34	3000	3	Ra > 80	50.000	1513	3,50
6264.SR.5500/840/WD	3800	5500	112	34	4000	3	Ra > 80	50.000	1513	3,50