

Q-LA LED



Pendant LED luminaire

Mounting:	Suspended on 1,5m long wire suspension
Body material:	Steel and aluminium
Colour:	Standard Gray 9006, other RAL colours on request (please add RAL code after index number)
LED module:	LED module included
Colour temperature:	2700K, 3000K or 4000K available
Colour Rendering Index (CRI):	>80 in standard
Driver:	Electronic integrated driver
Emergency unit:	N/A
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	0°C... +40°C
IP Class:	IP20
Power:	220-240V 50/60Hz
Lighting direction:	Direct lighting
Reflector type:	Aluminium
Light distribution:	Symmetric
General data:	5 Years standard warranty

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3771.800/827	800	10	2700	Ra > 80	50.000	5	3	0,60
3771.800/830	800	10	3000	Ra > 80	50.000	5	3	0,60
3771.800/840	800	10	4000	Ra > 80	50.000	5	3	0,60

