

REMY WALL MINI



Wall mounted direct / indirect LED luminaire

Mounting:	Wall mounted
Body material:	Steel and aluminium
Colour:	Standard Gray 9006, other RAL colours on request (please add RAL code after index number)
LED module:	LED module included
Colour temperature:	2700K or 3000K
Colour Rendering Index (CRI):	>80 in standard, other on request
Driver:	Electronic driver
Emergency unit:	N/A
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	0°C ... +40°C
IP Class:	IP20 in standard, IP44 on request
Power:	220-240V 50/60Hz
Lighting direction:	Direct / indirect
Reflector type:	Integrated lens
Light distribution:	Symmetric
General data:	3 Years standard warranty
	Different lumen output or wattage available on request
	All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist
	Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

IP20 220-240 V
50-60 Hz



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5630.420/827	420	6	2700	Ra > 80	50.000	5	3	1,00
5630.420/830	420	6	3000	Ra > 80	50.000	5	3	1,00

