

SQUARE 700 LED LINE


Surface mounted or Suspended LED luminaire with direct or direct / indirect lighting.

- Mounting:** Directly on the ceiling - index nr. 3505.XXXX
Suspended - index nr. 3505.PND.XXXX, suspension wires included
Suspended direct / indirect - index nr. 3505.UD.XXXX, suspension wires included
- Body material:** Aluminium profile
- Colour:** Standard Gray 9006, other RAL colours on request (please add RAL code after index number)
- LED module:** Philips / Osram or Tridonic LED module included
- Colour temperature:** 3000K or 4000K
- Colour Rendering Index (CRI)** >80 in standard, other on request
- Driver:** Electronic driver in standard, DALI on request
- Emergency unit:** on request - Standard or DALI 3 hour emergency unit
- Movement sensor:** on request
- Daylight control sensor:** on request
- Operating temperature range:** 0°C ... +40°C
- IP Class:** IP20 in standard, IP44 on request
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct index nr. 3505.XXXX or Direct / indirect - index nr. 3505.UD.XXXX
- Reflector type:** Aluminium white
- Light distribution:** Symmetric
- Diffuser:** White acrylic diffuser [WD] in standard, acrylic frosted [AC], microprismatic [MPR] or any other on request.

- General data:** 5 Years standard warranty
UGR<19 diffuser on request
Different lumen output or wattage available on request
All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist
Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.
System power consumption (LED module & driver) depends on components used



Available versions



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3505.5000/830	5000	38	3000	Ra > 80	50.000	5	3	5,50
3505.5000/840	5000	38	4000	Ra > 80	50.000	5	3	5,50
PENDANT								
3505.PND.5000/830	5000	38	3000	Ra > 80	50.000	5	3	5,50
3505.PND.5000/840	5000	38	4000	Ra > 80	50.000	5	3	5,50
UP/DN								
3505.UD.9400/830	9400	67	3000	Ra > 80	50.000	5	3	5,50
3505.UD.9400/840	9400	67	4000	Ra > 80	50.000	5	3	5,50

