

TANGO



Ground mounted IP65 LED luminaire.

Mounting:	Directly on the ground, mounting base in the bottom of the luminaire
Body material:	Osram or equivalent
Colour:	Standard Dark Gray 7016, other RAL colours on request (please add RAL code after index number)
LED module:	Osram or equivalent
Colour temperature:	3000K or 4000K
Colour Rendering Index (CRI):	>80 in standard
Driver:	Electronic integrated driver
Emergency unit:	N/A
Movement sensor:	On request
Daylight control sensor:	N/A
Operating temperature range:	- 20°C ... +40°C
IP Class:	IP65
Power:	220-240V 50/60Hz
Lighting direction:	Direct
Reflector type:	N/A
Light distribution:	Asymmetric
Diffusor:	PMMA White diffusor
General data:	5 Years standard warranty

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

Efficacy depends on type of LED's, electronics, optics and diffusor and may differ from shown in our data pages. Most up to date information can be found in our lighting data file database.



Index no.	Net lumen output [lm]	Gross lumen output [lm]	Efficacy [lm/W]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	MacAdam [SDCM]	Weight [kg]
7618.1500/830	600	1500	46	13	3000	Ra > 80	50.000	4	4,70
7618.1500/840	600	1500	46	13	4000	Ra > 80	50.000	4	4,70

