

TRYTON

Suspended direct or direct / indirect LED luminaire, can be made to measure according to project requirements.

- Mounting:** Suspended on 1,5m long steel wire suspension (with wire length control)
- Body material:** Aluminium profile
- Colour:** Standard Gray 9006, other RAL colours on request (please add RAL code after index number)
- LED module:** Signify (Philips), Osram, Tridonic or equivalent LED module included
- Colour temperature:** 3000K or 4000K in standard, other on request
- Colour Rendering Index (CRI)** >80 in standard, other on request
- Driver:** Electronic driver in standard, DALI on request
- Emergency unit:** Standard or DALI, 3 hour emergency unit on request
- Movement sensor:** On request
- Daylight control sensor:** On request
- Operating temperature range:** 0°C ... +40°C
- IP Class:** IP20 in standard, IP44 on request
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct or direct / indirect
- Reflector type:** Aluminium white
- Light distribution:** Symmetric
- Diffuser:** [WD] white opalic in standard, Microprismatic [MPR] on request
- General data:** 5 Years standard warranty
UGR <19 diffuser on request
Different lumen output or wattage available on request
All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist
Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.
System power consumption (LED module & driver) depends on components used
Efficacy depends on type of LED's, electronics, optics and diffuser and may differ from shown in our data pages. Most up to date information can be found in our lighting data file database.



BESPOKE SIZE & PRODUCT FEATURES AVAILABLE

Index no.	Net lumen output [lm]	Gross lumen output [lm]	Efficacy [lm/W]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	MacAdam [SDCM]	Weight [kg]
PND DN									
7580.9900/830	6800	9900	113	60	3000	Ra > 80	50.000	3	8,00
7580.9900/840	6800	9900	113	60	4000	Ra > 80	50.000	3	8,00
7580.13200/830	9000	13200	110	82	3000	Ra > 80	50.000	3	8,00
7580.13200/840	9000	13200	110	82	4000	Ra > 80	50.000	3	8,00
7580.16500/830	11300	16500	113	100	3000	Ra > 80	50.000	3	8,00
7580.16500/840	11300	16500	113	100	4000	Ra > 80	50.000	3	8,00

[WD] diffuser



[MPR] diffuser

