

## **TUBIO 60 LED PND**





	Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
	5359.710/827	710	9,2	2700	Ra > 80	15.000	3	4	1,90
	5359.740/830	740	9,2	3000	Ra > 80	15.000	3	4	1,90
	5359 780/8/10	780	9.2	4000	Da > 80	15 000	3	/1	190

Pendant LED luminaire

Colour:

Suspended on 1,5m long steel wire suspension ( with wire length control ) Mounting:

Body material: Steel and aluminium

Standard Black / Orange, other

RAL colours on request ( please add RAL code after index

number)

LED GU10 retrofit lamp LED module:

included

2700K , 3000K or 4000K available Colour temperature:

Colour Rendering Index (CRI):  $>\!80$  in standard, other on

request

N/A N/A Emergency unit: Movement sensor: N/A Daylight control sensor: N/A

Operating temperature range:

0°C ... +40°C

IP Class: IP20

Power: 220-240V 50/60Hz

Lighting direction: Direct Reflector type: N/A Light distribution: Symmetric

General data: 3 Years standard warranty

> Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

