

## **UNO SURF INS GU10**





	Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
	5863.355/827/36D	355	4,6 W	2700	Ra > 80	15.000	3	4	0,60
ı	5863.370/830/36D	370	4,6 W	3000	Ra > 80	15.000	3	4	0,60
	5863.390/840/36D	390	4,6 W	4000	Ra > 80	15.000	3	4	0,60

## Surface mounted LED luminaire.

Colour:

Directly on the ceiling Mounting: Body material: Steel and aluminium

Standard Gray RAL 9006, other

RAL colours on request (please add RAL colour after index

number)

LED GU10 retrofit lamp LED module:

included

2700K , 3000K or 4000K available Colour temperature:

Colour Rendering Index (CRI) >80 in standard, other on request

Driver: N/A N/A Emergency unit: Movement sensor: N/A Daylight control sensor: N/A

Operating temperature range:

0°C ... +40°C

IP Class: IP20

Power: 220-240V 50/60Hz Lighting direction: Direct lighting Light distribution: Symmetric

General data: 3 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

