

# XLN 360

Surface mounted LED luminaire with direct lighting.

<b>Mounting:</b>	Directly on the ceiling
<b>Body material:</b>	Steel and aluminium
<b>Colour:</b>	Standard White RAL 9016, other RAL colours on request (please add RAL colour after index number)
<b>LED module:</b>	Signify (Philips), Osram, Tridonic or equivalent LED module included
<b>Colour temperature:</b>	3000/4000K, other on request
<b>Colour Rendering Index (CRI):</b>	>80 in standard, other on request
<b>Driver:</b>	EVG/DALI on request
<b>Emergency unit:</b>	On request - Standard or DALI 3 hour emergency unit
<b>Movement sensor:</b>	on request
<b>Daylight control sensor:</b>	on request
<b>Operating temperature range:</b>	0°C ... +40°C
<b>IP Class:</b>	IP44
<b>Power:</b>	220-240V 50/60Hz
<b>Lighting direction:</b>	Direct lighting
<b>Reflector type:</b>	Aluminium white
<b>Light distribution:</b>	Symmetric
<b>Diffuser:</b>	OP (Opal), MP (Microprismatic), MP19 (Microprismatic with UGR<19)
<b>General data:</b>	5 Years standard warranty


Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist


Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

Efficacy depends on type of LED's, electronics, optics and diffuser and may differ from shown in our data pages. Most up to date information can be found in our lighting data file database.



## Drawing



Energy saving MasterConnect wireless lighting control system with daylight and movement detection technology on request.




Zigbee



Bluetooth

Available versions



XLN 360

Product code	Product name	Gross Lumen [lm]	Nett Lumen [lm]	Power [W]	Efficacy [lm/W]	Colour temperature [K]	Length [mm]	Width [mm]	Height [mm]	Nett Weight [kg]
Ceiling mounted luminaire, light down										
20.00120.83.E.OP	XLN 360 4400lm/830/E/OP	4400	3300	31	106	3000	360	360	60	2,9
20.00120.84.E.OP	XLN 360 4400lm/840/E/OP	4400	3300	31	106	4000	360	360	60	2,9
20.00120.83.E.MP	XLN 360 4400lm/830/E/MP	4400	3300	31	106	3000	360	360	60	2,9
20.00120.84.E.MP	XLN 360 4400lm/840/E/MP	4400	3300	31	106	4000	360	360	60	2,9
20.00120.83.E.MP19	XLN 360 4400lm/830/E/MP19	4400	3300	31	106	3000	360	360	60	2,9
20.00120.84.E.MP19	XLN 360 4400lm/840/E/MP19	4400	3300	31	106	4000	360	360	60	2,9