

# TUBE 55 TRACK



Track mounted luminaire with selection of reflectors and variety of beam angles. Top quality COB LED module with colour consistency MacAdams  $\leq 3$ , extensive portfolio of lumen ranges, CCTs and spectra. Variety of track adaptor integrated drivers: standard EVG on/off, DALI and wireless controled as MasterConnect or Casambi on request. Remote, wireless occupancy & daylight sensor available to allow significant energy savings and wireless connectivity. Mounting on universal track systems: Global / Unipro. Track adaptor for any other type of track system on request. Body is made of aluminium and steel. Standard colour RAL 9005S, any other colour from basic RAL range available at no extra cost. Variety of optics, lumen outputs and drivers allows to use this luminaire in different types of lighting projects. Luminous flux & Luminaire Power tolerance up to 10%. System power consumption depends on components used. Luminous efficacy depends on type of LED's, electronics, optics and diffusor. The most up to date technical parameters can be found on our website and in database of LDT files.

Lighting direction



PDF datasheet:



# TUBE 55 TRACK

<b>Mounting:</b>	Track mounted
<b>Body material:</b>	Steel and aluminium
<b>Colour:</b>	Standard black RAL 9005S, other RAL colours on request
<b>Lumen output:</b>	Standard up to 2000 lm, any other on request
<b>LED module:</b>	Signify (Philips), Tridonic or equivalent COB LED modules
<b>Colour temperature:</b>	2700/3000/4000K, other on request
<b>Colour Rendering:</b>	CRI>80 in standard, other on request
<b>Driver:</b>	EVG on-off/DALI/MC ( MasterConnect )/Casambi, other on request
<b>Wireless control:</b>	Philips MasterConnect / Casambi, other on request
<b>Daylight/Occupancy sensor:</b>	Wireless ICS sensor
<b>Emergency unit:</b>	N/A
<b>Operating temperature range:</b>	0°C ... +35°C
<b>IP Class:</b>	IP20 in standard
<b>Power:</b>	220-240V 50/60Hz
<b>Lighting direction:</b>	Direct
<b>Light distribution:</b>	Symmetric
<b>Optics:</b>	Reflector
<b>Beam angle:</b>	16°/26°/40°/60°
<b>Warranty:</b>	5 Years standard warranty

**TUBE 55 TRACK** track mounted luminaire  
**TUBE 55 TRACK L** track mounted luminaire / long tube

All current index numbers, lumen outputs, power consumption and many other technical information are available in our 2024 pricelist. Details on wireless lighting control systems on page number 896.



**Energy saving MasterConnect wireless lighting control system with daylight and movement detection technology on request.**

 Zigbee  Bluetooth



LP long mounting pipe 500 mm



CRB ceiling recessed base




CMB ceiling mounting base



ICS wireless daylight&occ sensor



ICSW wireless switch



Basic dimensions



## TUBE 55 TRACK

Product code	Product name	Gross Lumen [lm]	Nett Lumen [lm]	Power [W]	Efficacy [lm/W]	Colour temperature [K]	Optics	Diameter [mm]	Height [mm]	Nett Weight [kg]
30.00760.83.ET.15.LNS	TUBE 55 TRACK / 800lm / 830 / ET / 15	800	690	5	138	3000	15°	Ø 55	165	0,7
30.00760.83.ET.25.LNS	TUBE 55 TRACK / 800lm / 830 / ET / 25	800	690	5	138	3000	25°	Ø 55	165	0,7
30.00760.83.ET.39.LNS	TUBE 55 TRACK / 800lm / 830 / ET / 39	800	690	5	138	3000	39°	Ø 55	165	0,7
30.00760.83.ET.61.LNS	TUBE 55 TRACK / 800lm / 830 / ET / 61	800	690	5	138	3000	61°	Ø 55	165	0,7
30.00760.84.ET.15.LNS	TUBE 55 TRACK / 800lm / 840 / ET / 15	800	690	5	138	4000	15°	Ø 55	165	0,7
30.00760.84.ET.25.LNS	TUBE 55 TRACK / 800lm / 840 / ET / 25	800	690	5	138	4000	25°	Ø 55	165	0,7
30.00760.84.ET.39.LNS	TUBE 55 TRACK / 800lm / 840 / ET / 39	800	690	5	138	4000	39°	Ø 55	165	0,7
30.00760.84.ET.61.LNS	TUBE 55 TRACK / 800lm / 840 / ET / 61	800	690	5	138	4000	61°	Ø 55	165	0,7
30.00761.83.ET.15.LNS	TUBE 55 TRACK / 1500lm / 830 / ET / 15	1500	1290	9	143	3000	15°	Ø 55	165	0,7
30.00761.83.ET.25.LNS	TUBE 55 TRACK / 1500lm / 830 / ET / 25	1500	1290	9	143	3000	25°	Ø 55	165	0,7
30.00761.83.ET.39.LNS	TUBE 55 TRACK / 1500lm / 830 / ET / 39	1500	1290	9	143	3000	39°	Ø 55	165	0,7
30.00761.83.ET.61.LNS	TUBE 55 TRACK / 1500lm / 830 / ET / 61	1500	1290	9	143	3000	61°	Ø 55	165	0,7
30.00761.84.ET.15.LNS	TUBE 55 TRACK / 1500lm / 840 / ET / 15	1500	1290	9	143	4000	15°	Ø 55	165	0,7
30.00761.84.ET.25.LNS	TUBE 55 TRACK / 1500lm / 840 / ET / 25	1500	1290	9	143	4000	25°	Ø 55	165	0,7
30.00761.84.ET.39.LNS	TUBE 55 TRACK / 1500lm / 840 / ET / 39	1500	1290	9	143	4000	39°	Ø 55	165	0,7
30.00761.84.ET.61.LNS	TUBE 55 TRACK / 1500lm / 840 / ET / 61	1500	1290	9	143	4000	61°	Ø 55	165	0,7
30.00762.83.ET.15.LNS	TUBE 55 TRACK L / 800lm / 830 / ET / 15	800	690	5	138	3000	15°	Ø 55	500	1,5
30.00762.83.ET.25.LNS	TUBE 55 TRACK L / 800lm / 830 / ET / 25	800	690	5	138	3000	25°	Ø 55	500	1,5
30.00762.83.ET.39.LNS	TUBE 55 TRACK L / 800lm / 830 / ET / 39	800	690	5	138	3000	39°	Ø 55	500	1,5
30.00762.83.ET.61.LNS	TUBE 55 TRACK L / 800lm / 830 / ET / 61	800	690	5	138	3000	61°	Ø 55	500	1,5
30.00762.84.ET.15.LNS	TUBE 55 TRACK L / 800lm / 840 / ET / 15	800	690	5	138	4000	15°	Ø 55	500	1,5
30.00762.84.ET.25.LNS	TUBE 55 TRACK L / 800lm / 840 / ET / 25	800	690	5	138	4000	25°	Ø 55	500	1,5
30.00762.84.ET.39.LNS	TUBE 55 TRACK L / 800lm / 840 / ET / 39	800	690	5	138	4000	39°	Ø 55	500	1,5
30.00762.84.ET.61.LNS	TUBE 55 TRACK L / 800lm / 840 / ET / 61	800	690	5	138	4000	61°	Ø 55	500	1,5
30.00763.83.ET.15.LNS	TUBE 55 TRACK L / 1500lm / 830 / ET / 15	1500	1290	9	143	3000	15°	Ø 55	500	1,5
30.00763.83.ET.25.LNS	TUBE 55 TRACK L / 1500lm / 830 / ET / 25	1500	1290	9	143	3000	25°	Ø 55	500	1,5
30.00763.83.ET.39.LNS	TUBE 55 TRACK L / 1500lm / 830 / ET / 39	1500	1290	9	143	3000	39°	Ø 55	500	1,5
30.00763.83.ET.61.LNS	TUBE 55 TRACK L / 1500lm / 830 / ET / 61	1500	1290	9	143	3000	61°	Ø 55	500	1,5
30.00763.84.ET.15.LNS	TUBE 55 TRACK L / 1500lm / 840 / ET / 15	1500	1290	9	143	4000	15°	Ø 55	500	1,5
30.00763.84.ET.25.LNS	TUBE 55 TRACK L / 1500lm / 840 / ET / 25	1500	1290	9	143	4000	25°	Ø 55	500	1,5
30.00763.84.ET.39.LNS	TUBE 55 TRACK L / 1500lm / 840 / ET / 39	1500	1290	9	143	4000	39°	Ø 55	500	1,5
30.00763.84.ET.61.LNS	TUBE 55 TRACK L / 1500lm / 840 / ET / 61	1500	1290	9	143	4000	61°	Ø 55	500	1,5