## CLIN 1200 SURF OP





Rectangular surface mounted cleanroom luminaire. Diffusor-opal acrylic and clear tempered glass. Top quality SMD LED modules with colour consistency MacAdams 3, extensive portfolio of lumen ranges, CCTs and spectra. Variety of drivers: standard EVG on/off, DALI, TW DT8 on request. Mounting on any type of ceiling. Body is made of aluminium and steel. Standard colour RAL 9003M antibacterial paint, other colours on reguest. Variety of lumen outputs and drivers allows to use this luminaire in different types of lighting projects.

Luminous flux & Luminaire Power tolerance up to 10%. System power consumption depends on components used. Luminous efficacy depends on type of LED's, electronics, optics and diffusor. The most up to date technical parameters can be found on our website and in database of LDT files.

Lighting direction

PDF datasheet:






## CLIN 1200 SURF OP

Mounting:	Surface mounting
Body material:	Steel and aluminium
Colour:	Standard white RAL 9003, other RAL colours on request
Lumen output:	Standard up to 10.000 lm, any other on request
LED module:	Signify (Philips), Tridonic or equivalent SMD LED modules
Colour temperature:	3000/4000K/2700-6500K TunableWhite, other on request
Colour Rendering:	CRI>80 in standard, other on request
Driver:	EVG on-off/DALI/TW DT8, other on request
Wireless controll:	On request
Daylight/Occupancy sensor:	On request
Emergency unit:	On request
Emergency unit: Operating temperature range:	On request O°C +35°C
•••	
Operating temperature range:	0°C +35°C
Operating temperature range: IP Class:	0°C +35°C IP65 in standard
Operating temperature range: IP Class: Power:	0°C +35°C IP65 in standard 220-240V 50/60Hz
Operating temperature range: IP Class: Power: Lighting direction:	0°C +35°C IP65 in standard 220-240V 50/60Hz Direct lighting
Operating temperature range: IP Class: Power: Lighting direction: Light distribution:	0°C +35°C IP65 in standard 220-240V 50/60Hz Direct lighting Symmetric
Operating temperature range: IP Class: Power: Lighting direction: Light distribution: Optics:	0°C +35°C IP65 in standard 220-240V 50/60Hz Direct lighting Symmetric White reflector
Operating temperature range: IP Class: Power: Lighting direction: Light distribution: Optics: Beam angle:	0°C +35°C IP65 in standard 220-240V 50/60Hz Direct lighting Symmetric White reflector All types available in our LDT file database

## CLIN 1200 SURF OP surface mounted luminaire

All current index numbers, lumen outputs, power consumption and many other technical information are available in our 2024 pricelist.



Basic dimensions