

## **SNAKE 3**











Snake shaped, suspended luminaire. Top quality SMD LED modules with colour consistency MacAdams sale extensive portfolio of lumen ranges, CCTs and spectra. Variety of drivers: standard EVG on/off, DALI and wireless controlled as MasterConnect or Casambi on request. Built-in or remote, wireless occupancy & daylight sensor available to allow significant energy savings and wireless connectivity. Mounting on any type of ceiling. Body is made of rolled aluminium profile. Standard colour RAL 9003S, any other colour from basic RAL range available at no extra cost. Variety of sizes, diffusors, lumen outputs and drivers allows to use this luminaire in different types of lighting projects.

Luminous flux & Luminaire Power tolerance up to 10%. System power consumption depends on components used. Luminous efficacy depends on type of LED's, electronics, optics and diffusor. The most up to date technical parameters can be found on our website and in database of LDT files.

Lighting direction:



PDF datasheet:





## **SNAKE 3**

Mounting: Suspended Body material: Aluminium profile

Standard white RAL 9003S, other RAL colours on request Colour:

Lumen output: Standard up to 33.000 lm, any other on request

LED module: Signify (Philips), Tridonic or equivalent SMD LED module

3000/4000K/2700-6500K TW, other on request Colour temperature:

Colour Rendering: CRI>80 in standard, other on request

Driver: EVG on-off/DALI/TW DT8/MC (MasterConnect)/Casambi, other on request

Philips MasterConnect / Casambi, other on request Wireless controll:

Daylight/Occupancy sensor: Built-in XC sensor or wireless MCS sensor

**Emergency unit:** On request Operating temperature range: 0°C ... +35°C IP Class: IP20 in standard 220-240V 50/60Hz Power: Lighting direction: Direct lighting Light distribution: Symmetric

Diffuser: OP white acrylic, MP19H microprismatic UGR<19 All types available in our LDT file database Beam angle:

Warranty: 5 Years standard warranty

## SNAKE3 suspended, light down



Energy saving MasterConnect wireless lighting control system with daylight and movement detection technology on request.





All current index numbers, lumen outputs, power consumption and many other technical information are available in our 2024 pricelist. Details on wireless lighting control systems on page number 896.



XC daylight&occ sensor



OP opal diffusor




MP19H microprismatic diffusor



MCS wireless daylight&occ sensor



XCS wireless switch



Basic dimensions