

COIN TUBE 2



Wall mounted, cylindrical IP65 luminaire with high quality lens optics. Top quality SMD LED module with colour consistency MacAdams 3, extensive portfolio of lumen ranges, CCTs and spectra. Standard EVG on/off integrated driver. Mounting on any type of wall. Body is made of aluminium. Standard colour RAL 7016 any other colour from basic RAL range available at no extra cost. Selection of beam angles and lumen outputs allows to use this luminaire in different types of lighting projects. Standard luminaire is not intended for use in increased corrosivity category environment, e.g. with increased salt concentration. Extra corrosion protection is available on request.

Luminous flux & Luminaire Power tolerance up to 10%. System power consumption depends on components used. Luminous efficacy depends on type of LED's, electronics, optics and diffusor. The most up to date technical parameters can be found on our website and in database of LDT files.

Lighting direction



PDF datasheet:



COIN TUBE 2


Mounting:	Wall mounting
Body material:	Aluminium
Colour:	Standard anthracite grey RAL 7016, other RAL colours on request
Lumen output:	Standard up to 1800 lm, any other on request
LED module:	Osram SMD LED module
Colour temperature:	3000/4000K, other on request
Colour Rendering:	CRI>80 in standard, other on request
Driver:	EVG on-off integrated, other on request
Wireless control:	N/A
Daylight/Occupancy sensor:	N/A
Emergency unit:	N/A
Operating temperature range:	-20°C ... +40°C
IP Class:	IP65 in standard
Power:	220-240V 50/60Hz
Lighting direction:	Direct/indirect lighting
Light distribution:	Symmetric
Optics:	Lens
Beam angle:	24°/40°
Diffuser:	CG clear glass
Warranty:	5 Years standard warranty

COIN TUBE 2 wall mounted luminaire, light up and down

All current index numbers, lumen outputs, power consumption and many other technical information are available in our 2024 pricelist.



Custom made wall bracket



Basic dimensions