

## TANKLIGHT SQ











Outdoor, canopy IP65 luminaire with lense optics. Body is made of aluminium, diffusor of clear, tempered glass. Top quality SMD LED modules with colour consistency MacAdams 3, extensive portfolio of lumen ranges, CCTs and spectra. Variety of drivers: standard EVG on/off, DALI and wireless controlled as MasterConnect on request. Buil-in or remote IP65, wireless occupancy & daylight sensor available to allow significant energy savings and wireless connectivity. Mounting in any type of ceiling. Standard colour RAL 9003, any other on request. Variety of optics, lumen outputs and drivers allows to use this luminaire in different types of lighting projects. Standard luminaire is not intended for use in increased corrosivity category environment, e.g. with increased salt concentration. Extra corrosion protection is available on request.

Luminous flux & Luminaire Power tolerance up to 10%. System power consumption depends on components used. Luminous efficacy depends on type of LED's, electronics, optics and diffusor. The most up to date technical parameters can be found on our website and in database of LDT files.

Lighting direction



PDF datasheet:





## TANKLIGHT SQ

**Mounting:** Recessed mounting, custom made brackets on request

Body material: Aluminium

Colour: Standard white RAL 9003, other RAL colours on request

**Lumen output:** Standard up to 14.000 lm, any other on request

**LED module:** Signify (Philips), Tridonic or equivalent SMD LED module

 Colour temperature:
 3000/4000K, other on request

 Colour Rendering:
 CRI>80 in standard, other on request

**Driver:** EVG on-off, DALI, other on request

Operating temperature range: -30°C ... +45°C

IP Class: IP65 in standard

Power: 220-240V 50/60Hz

Lighting direction: Direct lighting

Light distribution: Symmetric

Optics: Lens


Beam angle: Wide selection of optics - please refer to our LDT database

Diffuser: CG clear glass

Warranty: 5 Years standard warranty

## TANKLIGHT SQ recessed mounted luminaire

All current index numbers, lumen outputs, power consumption and many other technical information are available in our 2024 pricelist.



Basic dimensions