

DLK 200



Recessed LED downlight for installation in suspended ceilings.

- Mounting:** Ceiling recessed, mounting brackets included
- Body material:** Steel and aluminium
- Colour:** Standard White RAL 9016, other RAL colours on request (please add RAL colour after index number)
- LED module:** LED module included
- Colour temperature:** 3000K or 4000K available
- Colour Rendering Index (CRI):** >80 in standard, other on request
- Driver:** Electronic Integrated driver
- Emergency unit:** N/A
- Movement sensor:** N/A
- Daylight control sensor:** N/A
- Operating temperature range:** 0°C ... +40°C
- IP Class:** IP44
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct lighting
- Reflector type:** Aluminium glossy
- Light distribution:** Symmetric
- Diffuser:** Altuglas [ALT] opalic diffusor in standard
- General data:** 5 Years standard warranty, possible extension with project registration

Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



| Index no. | Lumen output [lm] | Power [W] | Colour temp. [K] | CRI | Lifetime [H] | Warranty [Years] | MacAdam [SDCM] | Weight [kg] |
|----------------------------------|-------------------|-----------|------------------|---------|--------------|------------------|----------------|-------------|
| With integrated AC driver | | | | | | | | |
| 6500.1100/830 | 1100 | 10 | 3000 | Ra > 80 | 50.000 | 5 | 3 | 2,10 |
| 6500.1100/840 | 1100 | 10 | 4000 | Ra > 80 | 50.000 | 5 | 3 | 2,10 |
| 6500.2000/830 | 2000 | 18 | 3000 | Ra > 80 | 50.000 | 5 | 3 | 2,10 |
| 6500.2000/840 | 2000 | 18 | 4000 | Ra > 80 | 50.000 | 5 | 3 | 2,10 |
| 6500.3000/830 | 3000 | 27 | 3000 | Ra > 80 | 50.000 | 5 | 3 | 2,10 |
| 6500.3000/840 | 3000 | 27 | 4000 | Ra > 80 | 50.000 | 5 | 3 | 2,10 |
| With AC/DC driver | | | | | | | | |
| 6563.1100/830 | 1100 | 12 | 3000 | Ra > 80 | 50.000 | 5 | 3 | 2,30 |
| 6563.1100/840 | 1100 | 12 | 4000 | Ra > 80 | 50.000 | 5 | 3 | 2,30 |
| 6563.2000/830 | 2000 | 20 | 3000 | Ra > 80 | 50.000 | 5 | 3 | 2,30 |
| 6563.2000/840 | 2000 | 20 | 4000 | Ra > 80 | 50.000 | 5 | 3 | 2,30 |
| 6563.3200/830 | 3200 | 31 | 3000 | Ra > 80 | 50.000 | 5 | 3 | 2,30 |
| 6563.3200/840 | 3200 | 31 | 4000 | Ra > 80 | 50.000 | 5 | 3 | 2,30 |

