

KP 600 LED



Recessed LED luminaire for installation in modular suspended ceilings, version for gypsum ceiling on request.

Mounting:	Modular ceiling lay in type in standard, mounting brackets for gypsum ceiling on request.
Body material:	Steel and aluminium
Colour:	Standard White RAL 9016, other RAL colours on request (please add RAL colour after index number)
LED module:	Philips / Osram or Tridonic LED module included
Colour temperature:	3000K or 4000K
Colour Rendering Index (CRI)	>80 in standard, >90 on request
Driver:	Electronic driver in standard, DALI on request
Emergency unit:	On request - Standard or DALI 3 hour emergency unit
Movement sensor:	on request
Daylight control sensor:	on request
Operating temperature range:	0°C ... +40°C
IP Class:	IP20
Power:	220-240V 50/60Hz
Lighting direction:	Direct / indirect lighting
Reflector type:	White painted
Light distribution:	Symmetric
Diffuser:	Microprismatic [MPR] diffuser in standard
General data:	5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6502.4400/830	4400	29	3000	Ra > 80	50.000	5	3	5,00
6502.4400/830	4400	29	4000	Ra > 80	50.000	5	3	5,00

