

BULLET LED



Pendant LED luminaire

Mounting:	Suspended on 1,5m long wire suspension
Body material:	Steel and aluminium
Colour:	Standard Black 9005, other RAL colours on request (please add RAL code after index number)
LED module:	LED AR111 retrofit lamp included
Colour temperature:	2700K or 3000K
Colour Rendering Index (CRI):	>80 in standard
Driver:	Electronic driver
Emergency unit:	N/A
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	0°C ... +40°C
IP Class:	IP20
Power:	220-240V 50/60Hz
Lighting direction:	Direct lighting
Reflector type:	N/A
Light distribution:	Symmetric
General data:	3 Years standard warranty

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3787.610/827/24D	610	10	2700	Ra > 80	40.000	3	3	1,50
3787.610/830/40D	610	10	3000	Ra > 80	40.000	3	3	1,50
3787.800/827/24D	800	15	2700	Ra > 80	40.000	3	3	1,50
3787.760/827/40D	760	15	2700	Ra > 80	40.000	3	3	1,50

